P-21

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:
The corner was established by H. Gradon in 1881 under Contract No. 383. The original notes state:

DIAGRAM
T10S R32E
1/4
S23|S24

North between Sec 23 & 24
40.00 Set stone 20x8x5 for 1/4 sec cor from which
A pine 24 in dia bears N60°W 58 lks dist
A pine 30 in dia bears S57°E 55 lks dist

Description of corner evidence found:
Found a 12x8x6 unmarked stone in a mound of stone.
Roothole of a double pine bears N64°44'W 41.6 ft (N60°W 58 lks) face down.
Roothole of a pine bears S52°20'E 36.6 ft (S57°E 55 lks) blaze & chaining notch.

Description of monument and accessories I establish to perpetuate the original location of this corner:
Set a 2-1/4x30" aluminum monument 8" in the ground in a mound of stone & buried the original on the North side.
New BTs:
A 12" Pine bears N77°27'W 21.3 ft scribed 1/4S23BT.
An 8" Pine bears S33°17'E 15.1 ft scribed 1/4S24BT.

T10S R32E
1/4
S23|S24
PLS1918
1989

New BTs have 3/4" brass washers marked PLS1918 attached to the BT blaze, faces and bands painted with red tree marking paint, and BT tags and Attention or Land Survey Monument signs. A steel fence post with Attention or Land Survey Monument sign is driven approximately 3-5 feet from the corner.

Sun Cadastral Survey
Contract No.: 53-04H1-7-4011
Project No.: 8722LB
Field Book: 7-73
Work Accomplished: 6/8/89
Witnesses: Louise Parsons

PARSONS SURVEYING
1915 S.E. Stone Street
Corvallis, OR 97333
(503) 752-7515

REGISTERED
PROFESSIONAL
LAND SURVEYOR
OREGON
JULY 16, 1980
TYLER B. PARSONS
1918

Office of COUNTY SURVEYOR County of GRANT
State of OREGON, I hereby certify that the within instrument was filed in this office for record on the 10 day of Aug, 1989

Robert A. Bagett by _____
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

P-21
CS1095