CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1881 by H.D. Gradon & B. Robb
Set post for 1/4 Section from which
a pine, 10" in diam., bears N88°E, 7 lks.
a pine, 12" in diam., bears N65°W, 70 lks.

DIAGRAM

T10S R32E
S.C.
1/4 — S31

Description of corner evidence found:

Found 2"X2" post (Not original)
Found original bearing tree
Remains of Pine stump, N88°E, 4.62', Scribed 1/4S, B.T.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set 3" Aluminum cap on 2½" Aluminum pipe 30" long & buried 27" in ground

New Bearing Trees:

6" Black Pine, N22°W, 18.7', Scribed 1/4, S31, B.T.
8" Black Pine, N57°E, 18.5', Scribed 1/4, S31, B.T.

All B.T.'s have sign 54-4 & 54-3 attached. Set steel guard post with 54-9 sign 3' West of monument. Painted red band around bearing trees. Tagged trees with L.S. 980 washer.

Witnesses: David Scott, Party Chief
Harold Pavey, Chainman

MONUMENT STAMPED:

REGISTERED
PROFESSIONAL
LAND SURVEYOR
Edgar W. Graves
OREGON
JULY 14, 1972
EDGAR W. GRAVES
980

T10S R32E
SC
1/4 S31
1980
ORLS 980

Office of..... Surveyor ..... County of..... Grant .....
State of..... Oregon ....., I hereby certify that the within instrument was filed in this office
for record on the..... 2 ..... day of ..... Oct ..... , 19..80
..... Robert D. Bagot ..... by .....
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

☆ GPO—798-276

Z-3