

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. C-17

History of original corner establishment:

This corner was originally established by A.F. York under G.L.O. contract No. 371, in September of 1880. Notes state: Set stone 46"x38"x10" for 1/4 sec. cor., Raised stone mound at corner.

DIAGRAM
T11S R26E
1/4
S3 | S2
1996
PLS 848

Description of Corner Evidence Found:

Found a 40"x30"x10" faintly marked, set in a mound of stone. Corner falls 5' east of an old fence running south. Accepted this as the original corner.

Description of monument and accessories I established to perpetuate the original location of this corner:

At the position of the original stone, set a 3"x30" aluminum monument 16" deep and raised a 3.5'dia. x 1.5' high mound of stone. Placed the original stone North alongside the monument inside of the mound of stone.

From which:

Set 5/8"x30" rebar pins with yellow plastic caps stamped "P.L.S. 848 as follows:

N63°45'W, 50.9 ft.

N60°13'E, 22.7 ft.

S52°51'E, 14.4 ft.

S59°32'W, 38.6 ft.

Measurements to accessories taken with a Wild TC1600 Total station.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1993
DOUGLAS M. FERGUSON
848

Renewal date
12/31/98

This work was performed by:
Douglas M. Ferguson, PLS 848
Witnessed by: D. Mitchell Ferguson
and Brad Cates
Date:12/17/96

Office of Surveyor County of Grant
State of OR I hereby certify that the within instrument was
filed in this office for record on the 21 day of JAN, 1998
Robert D. Baggett by _____
(COUNTY OFFICIAL) (DEPUTY)

See Nos 1444

C-17