

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. C-19

History of original corner establishment:

This corner was not previously established.

DIAGRAM
T11S R26E
C1/4 S2
1996
PLS 848

Description of Corner Evidence Found:

NA

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 3"x30" aluminum monument 18" deep and raised a 2.5'dia. x 1' high mound fo stone

From which:


A Juniper 6" dia. bears N17°40'W, 194.6 ft., scribed C1/4 S2 BT

A Juniper 8" dia. bears N54°24'E, 102.3 ft., scribed C1/4 S2 BT


A Juniper 8" dia. bears S51°46'E, 107.4 ft., scribed C1/4 S2 BT

A Ponderosa Pine 12" dia. bears S79°03'W, 253.8 ft.,
scribed C1/4 S2 BT

Measurements to accessories taken with a Wild TC1600 Total station. Nailed a brass washer stamped PLS 848 on blaze above BT scribe as taken this survey. Nailed Bearing Tree signs above blaze and Land Survey Monument signs on back of each tree. Painted a 6" red band above Bearing Tree signs and painted blaze red.



This work was performed by:
Douglas M. Ferguson, PLS 848
Witnessed by: D. Mitchell Ferguson
and Brad Cates
Date:12/17/96



Renewal date:
12/31/98

Office of SURVEYOR County of GRANT
State of OR I hereby certify that the within instrument was
filed in this office for record on the 21 day of JAN, 1998
Robert D. Baggett by _____
(COUNTY OFFICIAL) (DEPUTY)

SEE HDS 1114

C-19