

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. X-13

History of original corner establishment:

Corner is originally established by
Aaron F. York, in 1880, under "General
Land Office" Contract No. 371.
Surveyor Generals Notes State:
Set Stone 16x16x12 for 1/4 Sec. Cor.
Raised Stone mound at Cor.

DIAGRAM

T11S R28E
1/4
S331S34
1986
RLS 848

Description of corner evidence found:

Found 16"x12"x6" stone, with faint but unmistakable
"1/4" on the face, in the center of an old mound of
stone.


There are no accessories originally established,
accepted the above described stone as the 1/4 Cor.

**Description of monument and accessories | established to perpetuate the
original location of this corner:**

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown
on the **DIAGRAM**, SET 20" in the ground, set the original stone North
alongside the pipe and placed a circle of stone filled with earth around
the pipe.

From Which:

A Fir 10" dia., Bears N51°W., 19.6 ft., scribed: 1/4 S33 BT
A Juniper 10" dia., Bears S84°E., 22.0 ft., scribed: 1/4 S34 BT
Measurements to trees taken with a metal tape and magnetic compass,
with Declination set off 20 deg. East.
Nailed a brass washer stamped RLS 848 on blaze above BT scribe, Bearing
Tree Sign above blaze, and warning sign on back of each tree. Painted
a 6" red band at breast ht. around each tree. Set steel fence posts with
warning & Boundary Signs, North & South 6 ft. from the corner.



This work is performed by:
Douglas M. Ferguson RLS 848
Mt. Vernon Oregon.
On: Nov. 4, 1986
Refer to Map of Survey No. 965

Office of.....*Surveyor*..... County of.....*Grant*.....
State of.....*Oregon*..... I hereby certify that the within instrument was filed in this office
for record on the.....*18*..... day of.....*April*....., 19.....*87*.....
.....*Robert D. Baggett*..... by.....
(COUNTY OFFICIAL) (DEPUTY)