

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. C-9

History of original corner establishment
 Corner was originally established by
 W.H. Byars, in July & Aug., 1873, under
 General Land Office Contract No. 197.
 Surveyor Generals Notes State:
 Set a Basalt Stone 18x12x6, for the 1/4
 Section Corner.

DIAGRAM
 T11S R30E
 1/4
 |
 S5.S4
 |
 1986
 PLS 848

In 1909, Micheal Spears, County Surveyor, re-established the 1/4 S5/S4, by measuring from the SW Cor of Sec. 4, Record measurements, N 1°33'W., 79.29 ch and East 80.00 ch, where he found the S.E. Corner of Section 33, falling S 4 lks. Page 25 of Survey Record Book 1, as on file in the Grant County Clerks Office State: Proceeded to temp. W 1/4 Cor. Sec. 4 and corrected 11 lks. E. Set Rock 10x14x16, marked 1/4 CS., From Which:
 A Pine 8" dia. Bears S 1°15'W., 255 lks., marked BT CS
 A Pine 24" dia. Bears S70°55'E., 285 lks., marked BT CS


Description of corner evidence found:

Corner falls on the East edge of road 2 ft. West from N-S fence, all traces of the original stone and work by M. Spears, in 1909 is lost to road work and fencing. Even if the Corner as established by Spears was identified, its use in subdividing Section 4 would be questionable, as he did not follow a legal means of re-establishment.

The Corner is established as shown on this referenced Map of Survey No.934, of the Grant County Survey Records, by proportionate measure between the Section Corner found 1/2 mi. South and the Section Corner as found 1/2 mi. North, as shown by Map of Survey 784, of the Grant County Survey Records.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set 2-1/2"x30" aluminum pipe, with 3-1/2" aluminum cap, stamped as shown on the **DIAGRAM**, Set 2" in the ground and raised a mound of stone 4'x2' around the pipe.
 From Which:
 A Juniper 9" dia., Bears S87°56'E., 101.3 ft., scribed: 1/4 S4 BT
 A Juniper 10" dia., Bears N66°52'W., 76.6 ft., scribed: 1/4 S5 BT
 Measurements to trees Electronic Tacheometer, with angles turned from the survey control network.
 Nailed a brass washer stamped PLS 848 on blaze above BT scribe & Bearing Tree Sign above blaze,
 Painted a 6" red band at breast ht. around each tree.



This work is performed by:
 Douglas M. Ferguson PLS 848
 Mt. Vernon Oregon.
 On: May 8, 1986
 Refer to Map of Survey No. 934

INDEX. No. C-14.5

Office of.....*Surveyor*..... County of.....*Grant*.....
 State of.....*Oregon*....., I hereby certify that the within instrument was filed in this office
 for record on the...*22*... day of...*June*..., 19...*86*..
Robert D. Smith by
 (COUNTY OFFICIAL) (DEPUTY)