

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. D-11

History of original corner establishment:

Grant County Survey Records show no previous establishment of this Cor.

In 1909, Micheal Spears, County Surveyor, Subdivided this Section 4, whereby he set a temporary corner at this 1/16, but did not finally establish the corner.
See Survey Record Book 1, Page 25.

DIAGRAM

T11S R30E
C
S1/16S4
C
1986
PLS 848

Description of corner evidence found:

Grant County Survey Records show no previous establishment of this Cor.
(See "History of original corner established" above.)

Description of monument and accessories | established to perpetuate the original location of this corner:

Set 2-1/2"x30" aluminum pipe, with 3-1/2" aluminum cap, stamped as shown on the **DIAGRAM**, Set 26" in the ground.
From Which:
A Juniper 10" dia., Bears N50°W., 19.5 ft., scribed: C-S 1/16 S4 BT
A Pine 7" dia., Bears S42°E., 30.7 ft., scribed: C-S 1/16 S4 BT
Measurements to trees taken with a metal tape and magnetic compass, with Declination set off 20 deg. East.
Nailed a brass washer stamped PLS 848 on blaze above BT scribe & Bearing
Tree Sign above blaze,
Painted a 6" red band at breast ht. around each tree.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson PLS 848
Mt. Vernon Oregon.
On: May 8, 1986
Refer to Map of Survey No. 934

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 22 day of June, 1986
Robert H. Sager by _____
(COUNTY OFFICIAL) (DEPUTY)