

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. R-13

History of original corner establishment:

Corner was originally established by
Samual W. Lackland, in Sept. 1881,
under General Land Office Contract
No. 415.

The U.S. Surveyor Generals Notes State:
Set Basalt Stone 16x10x8 ins. 12 ins.
in ground for Cor to Secs. 21,22,27 & 28
marked with 2 notches on S & 3 notches on
E edges.

From Which

A Fir 12 ins diam bears N10°W., 34 lks dist marked T11S R30E S21 BT
A Fir 10 ins diam bears N50°E., 71 lks dist marked T11S R30E S22 BT
A Fir 28 ins diam bears S70°W., 75 lks dist marked T11S R30E S28 BT
A Fir 10 ins diam bears S35°E., 18 lks dist marked T11S R30E S27 BT

DIAGRAM

T11S R30E
S21:S22
-.-
S28:S27
1986
PLS 848

Description of corner evidence found:

Corner stone has been displaced by logging.
Found all four Bearing Trees and established the
Corner at the best overall fit to the trees, as
follows:

A 22" Fir, scribed R30E S21 Bears N 7°W, 22.4 ft.
A 26" Fir stump Bears N54°E., 46.0 ft.
A 24" Fir stump Bears S25°E., 11.0 ft.
A 36" Fir stump Bears S77°W., 50.0 ft.
All measurement to blaze face or face of trees.

**Description of monument and accessories | established to perpetuate the
original location of this corner:**

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown
on the **DIAGRAM**, SET 20" in the ground and placed stones and earth around
downhill side of the pipe.

From Which:

A Fir 16" dia., Bears N 8°W., 63.7 ft., scribed: T11S R30E S21 BT
A Fir 6" dia., Bears N87°E., 39.6 ft., scribed: S22 BT
A Fir 15" dia., Bears S19°E., 14.1 ft., scribed: T11S R30E S27 BT
A Fir 8" dia., Bears S52°W., 38.0 ft., scribed: T11S R30E S28 BT
Measurements to trees taken with a metal tape and magnetic compass,
with Declination set off 20 deg. East.
Nailed a brass washer stamped PLS 848 on blaze above BT scribe, Bearing
Tree Sign above blaze, and warning sign on back of each tree. Painted
a 6" red band at breast ht. around each tree. Set steel fence post with
warning Sign, North 5 ft. from the corner.

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

**OREGON
JULY 12, 1908
DOUGLAS M. FERGUSON
848**

This work is performed by:
Douglas M. Ferguson PLS 848
Mt. Vernon Oregon.
On: Sept. 8, 1986
Refer to Map of Survey No. 955

Office of Surveyor County of Grant
State of Oregon I hereby certify that the within instrument was filed in this office
for record on the 18 day of Dec, 1986
Robert D. Baggett by _____
(COUNTY OFFICIAL) (DEPUTY)