

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. S-9

History of original corner establishment:

Grant County Survey Records show no previous establishment of this Cor.

DIAGRAM

T11S R30E
N1/16
S29/S28
1986
PLS 848

Description of corner evidence found:

Grant County Survey Records show no previous establishment of this Cor.

Description of monument and accessories | established to perpetuate the original location of this corner:

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the **DIAGRAM**, SET 6" in the ground, and raised a mound of stone and earth around the pipe.



From Which:

A Pine 14" dia., Bears S29 E., 23.1 ft., scribed: N1/16 S28 BT

A Pine 16" dia., Bears S19⁰ W., 38.3 ft., scribed: N1/16 S29 BT

Measurements to trees taken with a metal tape and magnetic compass, with Declination set off 20 deg. East.

Nailed a brass washer stamped PLS 848 on blaze above BT scribe, Bearing Tree Sign above blaze, and warning sign on back of each tree. Painted a 6" red band at breast ht. around each tree. Set steel fence posts with warning & Boundary Signs, East 7 ft., and West 8 ft., from the corner.



This work is performed by:
Douglas M. Ferguson PLS 848
Mt. Vernon Oregon.
On: Sept. 1, 1986
Refer to Map of Survey No. 955

Office of Survey County of Grant
State of Oregon I hereby certify that the within instrument was filed in this office
for record on the 18 day of Sept, 1986
Douglas M. Ferguson by Douglas M. Ferguson
(COUNTY OFFICIAL) (DEPUTY)