

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. U-7

History of original corner establishment:

Grant County Survey Records show no previous establishment of this Cor.

DIAGRAM

T11S R30E
C
S1/16/S29
C
1986
PLS 848

Description of corner evidence found:

Grant County Survey Records show no previous establishment of this Cor.

Description of monument and accessories | established to perpetuate the original location of this corner:

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the **DIAGRAM**, SET 26" in the ground.

From Which:

A Juniper 10" dia., Bears S80°40'E., 44.7 ft., scribed: C-S 1/16 S29 BT

A Pine 16" dia., Bears S13°46'E., 103.4 ft., scribed: C-S 1/16 S29 BT

Measurements to trees taken with an Electronic Tacheometer with angles turned from the survey control network.

Nailed a brass washer stamped PLS 848 on blaze above BT scribe, Bearing Tree Sign above blaze, and warning sign on back of each tree. Painted a 6" red band at breast ht. around each tree. Set steel fence posts with warning & Boundary Signs, North 4 ft. & East 5 ft. from the corner.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1969
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson PLS 848
Mt. Vernon Oregon.
On: Sept. 5, 1986
Refer to Map of Survey No. 955

Office of.....*Surveyor*..... County of.....*Grant*.....
State of.....*Oregon*....., I hereby certify that the within instrument was filed in this office
for record on the.....*18* day of.....*Sept*....., 19.....*86*
.....*Robert D. Baggett*..... by.....
(COUNTY OFFICIAL) (DEPUTY)