

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. X-11

History of original corner establishment:

Grant County Survey Records show no previous establishment of this Cor.

DIAGRAM

T11S R30E
C1/4
S33
1985
PLS 848

Description of corner evidence found:

Grant County Survey Records show no previous establishment of this Cor.

Description of monument and accessories | established to perpetuate the original location of this corner:

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the **DIAGRAM**, SET 18" in the ground & raised a small mound of stone around the pipe.

From Which:

A Pine 10" dia., Bears N 9°W., 25.2 ft., scribed: C1/4 S33 BT

A Pine 8" dia., Bears N49°E., 15.8 ft., scribed: C1/4 S33 BT

Measurements to trees taken with a metal tape and magnetic compass, with Declination set off 20 deg. East.

Nailed a brass washer stamped PLS 848 on blaze above BT scribe, Bearing Tree Sign above blaze, and warning sign on back of each tree. Painted a 6" red band at breast ht. around each tree. Set steel fence post with warning Sign, North 1.8 ft., from the corner.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson PLS 848
Mt. Vernon Oregon,
On: Oct. 4, 1985
Refer to Map of Survey No. 904

Office of.....*Surveyor*..... County of.....*Grant*.....
State of.....*Oregon*....., I hereby certify that the within instrument was filed in this office
for record on the.....*22* day of.....*Dec*....., 19.....*85*
Robert D. Baggett by.....
(COUNTY OFFICIAL) (DEPUTY)