

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. X-14

History of original corner establishment:

Grant County Survey Records show no previous establishment of this Cor.

DIAGRAM

T11S R30E
W1/16
C--C
S34
1985
PLS 848

Description of corner evidence found:

Grant County Survey Records show no previous establishment of this Cor.

Description of monument and accessories | established to perpetuate the original location of this corner:

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the **DIAGRAM**, SET 26" in the ground.

From Which.

A Fir 10" dia., Bears S32°E., 25.0 ft., scribed: C-W 1/16 S34 BT

A Fir 10" dia., Bears N27°E., 37.2 ft., scribed: C-W 1/16 S34 BT

Measurements to trees taken with a metal tape and magnetic compass, with Declination set off 20 deg. East.

Nailed a brass washer stamped PLS 848 on blaze above BT scribe, Bearing Tree Sign above blaze, and warning sign on back of each tree. Painted a 6" red band at breast ht. around each tree. Set steel fence posts with warning & Boundary Signs, North & South 4 ft. from the corner.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson PLS 848
Mt. Vernon Oregon.

On: May 9, 1985

Refer to Map of Survey No. 904

Office of Surveyors County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 30 day of Dec, 1985
Robert D. Raggett by _____
(COUNTY OFFICIAL) (DEPUTY)