

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. Y-13

History of original corner establishment:

Grant County Survey Records show no previous establishment of this Cor.

DIAGRAM

T11S R30E
S1/16
|
S33. S34
|
1985
PLS 848

Description of corner evidence found:

Grant County Survey Records show no previous establishment of this Cor.

Description of monument and accessories | established to perpetuate the original location of this corner:

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the **DIAGRAM**, SET 24" in the ground.
From Which.

A Fir 12" dia., Bears S17°E., 26.3 ft., scribed: S1/16 S34 BT

A Fir 12" dia., Bears S20°W., 17.2 ft., scribed: S1/16 S33 BT

Measurements to trees taken with a metal tape and magnetic compass, with Declination set off 20 deg. East.

Nailed a brass washer stamped PLS 848 on blaze above BT scribe, Bearing Tree Sign above blaze, and warning sign on back of each tree. Painted a 6" red band at breast ht. around each tree. Set steel fence posts with warning & Boundary Signs, 5 ft. East & South from the corner.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson PLS 848
Mt. Vernon Oregon.
On: May 9, 1985
Refer to Map of Survey No. 904

Office of.....*Surveyor*..... County of.....*Grant*.....
State of.....*Oregon*....., I hereby certify that the within instrument was filed in this office
for record on the.....*20*..... day of.....*Dec*....., 19.....*85*.....
.....*Robert D. B. Galt*..... by.....
(COUNTY OFFICIAL) (DEPUTY)