

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. Z-18

History of original corner establishment:

Grant County Survey Records show no previous establishment of this Cor.

DIAGRAM
T115 R30E
S35
W1/16-.-
S2
T12S
RM 1 4.6
1985
PLS 848

Description of corner evidence found:

Grant County Survey Records show no previous establishment of this Cor.

Description of monument and accessories | established to perpetuate the

original location of this corner:

A Cluster of Pine Trees is at the Corner position, therefor set a 30"x5/8" iron pin with plastic cap, stamped: PLS 848 SURVEY MARKER.
From Which.

Set 2"x30" aluminum pipe, with 3-1/2" aluminum cap stamped as shown on the **DIAGRAM**, set 25" in the ground, Bears North 4.6 ft. from the corner.
A Pine 13" dia., Bears S10°W., 1.0 ft., from the cor., scribed: W1/16 S2 BT
A Pine 9" dia., Bears N26°E., 14.2 ft., from the cor., scribed: W1/16 S35 BT
Measurements to trees taken with a metal tape and magnetic compass, with Declination set off 20 deg. East.

Nailed a brass washer stamped PLS 848 on blaze above BT scribe, Bearing Tree Sign above blaze, and warning sign on back of each tree. Painted a 6" red band at breast ht. around each tree. Set steel fence posts with warning & Boundary Signs, North 9 ft. & West 7 ft. from the corner.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson PLS 848
Mt. Vernon Oregon.
On: Oct. 10, 1985
Refer to Map of Survey No. 904

Office of Surveyor County of Grant
State of Oregon I hereby certify that the within instrument was filed in this office
for record on the 20 day of Dec, 1985
Robert D. Gage by _____
(COUNTY OFFICIAL) (DEPUTY)