

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. Z-19
History of original corner establishment:

Corner originally established by
W.H. Byars, in 1873, under General
Land Office Contract No. 185.
Surveyor Generals Notes, State:
Set a Stone 12x12x5 for 1/4 Sec
cor.

DIAGRAM

T11S R30E
S35
1/4--
S2
T12S
1985
PLS 848

Description of corner evidence found:

Found 12"x6"x4" stone, set in a mound of stone,
with 1/4 marked on the North face.

From Which:

Found Bearing Trees as taken by Udell & Taylor
as follows:

A down & dead Fir 24" dia., Bears S15°E., 3.4 ft.

A Fir 20" dia. Bears N80°E., 54.7 ft.,

Since the stone is set and undisturbed it is accepted
as the 1/4 corner position.

**Description of monument and accessories established to perpetuate the
original location of this corner:**

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown
on the **DIAGRAM**, SET 18" in the ground and raised a mound of stone & earth
around the pipe.

From Which:

A Fir 13" dia., Bears N 9°W., 28.4 ft., scribed: 1/4 S35 BT

A Pine 17" dia., Bears S60°E., 23.6 ft., scribed: 1/4 S2 BT

Measurements to trees taken with a metal tape and magnetic compass,
with Declination set off 20 deg. East.

Nailed a brass washer stamped PLS 848 on blaze above BT scribe, Bearing
Tree Sign above blaze, and warning sign on back of each tree. Painted
a 6" red band at breast ht. around each tree. Set steel fence posts with
warning & Boundary Signs, North 8 ft., and South 12 ft., from the corner.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson PLS 848
Mt. Vernon Oregon.
On: Oct. 10, 1985
Refer to Map of Survey No. 904

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 20 day of Dec, 1985
Robert D. Dapth by _____
(COUNTY OFFICIAL) (DEPUTY)