


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. P-11

History of original corner establishment:

Grant County Survey Records show no previous establishment of this Cor.



Description of corner evidence found:

Grant County Survey Records show no previous establishment of this Cor.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the **DIAGRAM**, SET 8" in the ground & raised a mound of stone and earth around the pipe.

From Which:

Since no Bearing Trees are available, Set 5/8"x30" iron pins. with plastic caps stamped SURVEY MARKER PLS 848 and guard posts with warning, boundary & Bearing Tree signs, as follows:

North 9.7 ft. and South 4.4 ft. from the Corner.

Measurements to pins taken with a metal tape and magnetic compass, with Declination set off 20 deg. East.

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

[Signature]
**OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848**

This work is performed by:
Douglas M. Ferguson PLS 848
Mt. Vernon Oregon.
On: Sept. 26, 1985
Refer to Map of Survey No. 906

Office of *Surveyor* County of *Grant*
State of *Oregon*, I hereby certify that the within instrument was filed in this office
for record on the *2nd* day of *Dec*, 19*85*
Robert D. Begett by _____
(COUNTY OFFICIAL) (DEPUTY)