


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Original corner set by E.P. McCormack under contract number 398 dated July 2, 1881.

The government field notes state:

- 40.00 Set basalt stone 12 x 9 x 7 ins 8 ins in the ground for 1/4 sec cor marked 1/4 on W face from which  
A pine 30 ins diam bears N35°E 50 lks dist marked 1/4S BT.  
A tamarack 20 ins diam bears S85°W 10 lks dist marked 1/4S BT.



Description of corner evidence found:

- A stone 16" x 12" x 7" marked 1/4 on W face from which:  
A 29" DBH PP bears N35°E 34.1 ft., scribed 1/4.  
A 16" down tamarack bears S75°W 7.1 ft., scribed 1/4S BT.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 30" long 2-1/2" dia. aluminum pipe with 3-1/4" cap marked:  
22" in ground & erected a mound of stones around it. I buried the original stone monument face down, top to N, on the N side of the new monument, flush with ground.  
from which I scribe NEW BEARING TREES:

- A 13" DBH White fir bears S20°E 40.3 ft., scribed 1/4 S30 BT.  
A 17" DBH White fir bears N72°W 41.2 ft., scribed 1/4 S25 BT.

U.S. DEPT.  
OF AGRICULTURE  
UNLAWFUL TO DISTURB  
T11S  
R35-1/2E R36E  
1/4  
S25 + S30  
OPLS 1805  
1979  
CADASTRAL SURVEY  
FOREST SERVICE

I painted faces & bands around BT's red & attached BT & Attention tags & nailed a brass washer to the new BT blaze marked PLS 1805.  
I drove a 6 Ft. long steel fence post 2.3 Ft. in ground 6 Ft. N of corner & attached an attention tag to it.  
I used a steel tape & magnetic staff compass with 20° East variation, measuring to the center of the new BT's.  
This corner was set November 19, 1979.  
Witness: F.R. Palmer, S. Anderson & L.R. Nevill

Office of County Surveyor County of Grant  
State of Oregon, I hereby certify that the within instrument was filed  
in this office for record on the 4 day of Feb, 1980  
Robert D. Bayless by \_\_\_\_\_  
(COUNTY OFFICIAL) (DEPUTY)

