


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. A-25

History of original corner establishment:

Corner was originally established by Eugene McCormack under G.L.O. contract No. 398, August 4, 1881. Surveyor General's notes state: "At point of intersection I set a basalt stone 16x12x5 for closing corner to township 11 South, Range 35 and 36 East from which: A tamarack 6 ins. diam. bears S63°W, 20 lks. dist. A tamarack 6 ins. diam bears S60°E, 33 lks. dist."



When the Auxiliary Meridan was surveyed, the G.L.O. surveyor found the corner and describes the markings on the stone and bearing trees.

When the Second Standard Parallel South, through range 35 1/2 East was ran, the G.L.O. surveyor found and described the corner. He obliterated the scribing on the East bearing tree.

Description of corner evidence found:

In November, 1922, K.P. Cecil, National Forest Examiner was at the corner and marked a new bearing tree. "A fir 22 ins. diam. bears S43°W, 43 lks dist. marked T11SR35ES1 BT."


Found 16x12x7 inch stone firmly set in small mound of stone and clearly marked with 6 notches on E and W side and CC on South side.

Found 18" fir bearing S47°W, 28.8 ft. Partially opened blaze and partially visible scribing.

Found down and rotten lodgepole pine bearing S70°W, about 15 ft. and down and rotten lodgepole pine bearing S55°E, 25 ft. Both have scribing.

Corner is about 100 ft. south of highway.

Description of monument and accessories I established to perpetuate the original location of this corner:



At the center of the above stone, set 2 1/2" X 30" galvanized pipe and brass cap marked: Set pipe 24" in the ground and mound of stone around to cap. Placed mound of stone at base of pipe.

From which by magnetic declination of N20°E: An 18" tamarac bears N60°E, 42.9 ft. scribed T10SR351/2ES33 BT. Painted blazes red and 6" red band around. Placed 54-3s, 54-4s and brass washers stamped PLS 1051 on new BT. Placed 54-4 on steel fence post 5' west of the corner.

I hereby certify that the above corner monument was reestablished as herein described.

Witnesses: Robert Boling
Larry Shirley

July 21, 1980

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

Barry B. Barbour

**OREGON
OCT. 17, 1975
BARRY B. BARBOUR
1051**

Office of.....County Surveyor..... County of Grant
State of Oregon..... I hereby certify that the within instrument was filed in this office
for record on the 23rd day of January..... 1981
Robert B. Boling by
(COUNTY OFFICIAL) (DEPUTY)