

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. C-3

History of original corner establishment:

None. Corner established this survey.

DIAGRAM

T11S R35E  
C1/4  
•  
S 6  
1992  
PLS 2405

Description of Corner Evidence Found:

None. Corner established this survey.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set 2-1/2"x30" aluminum pipe with 3-1/4" aluminum cap, stamped as shown on the DIAGRAM, 14" in the ground and raised a mound of stone 1 1/2 ft. high x 2 1/2 ft. dia.

From Which:

- Ponderosa Pine, 10" dia., bears N67°46'W, 29.3 ft., scribed: C1/4 S6 BT
- Ponderosa Pine, 10" dia., bears N65°15'E, 37.9 ft., scribed: C1/4 S6 BT
- Douglas Fir, 12" dia., bears S72°45'E, 23.1 ft., scribed: C1/4 S6 BT
- Douglas Fir, 12" dia., bears S60°45'W, 4.2 ft., scribed: C1/4 S6 BT

Measurements to BT's taken with a magnetic compass, declination 20° East, and a nylon clad steel tape. Set steel fence post with Land Survey Monument (54-9) sign 5' north of the monument. Nailed a brass washer stamped PLS 2405 on blaze above BT scribe as taken this survey. Nailed Bearing Tree (54-3) signs above blaze and Land Survey Monument (54-9) signs on back of each tree as required. Painted a 6" red band above Bearing Trees signs and painted blaze red.

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*Susan E. Newstetter*

OREGON  
JULY 26, 1989  
SUSAN E. NEWSTETTER  
2405

Exp: 12/31/94

This work was performed by:  
Susan E. Newstetter PLS 2405  
Witnessed by: D. Mitchell Ferguson  
and Rick Saul  
November 4, 1992  
Refer to Grant Co. Survey No.: 1239

Office of Surveyor County of Grant  
State of OR I hereby certify that the within instrument was  
filed in this office for record on the 20 day of Jan, 1993  
Robert J. Dwyer by \_\_\_\_\_  
(COUNTY OFFICIAL) (DEPUTY)