

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. G-1

History of original corner establishment:

This corner was originally established by Bamford Robb and Herman D. Gradon, in 1881 under GLO Contract Number 383. Surveyor General Field Notes state:

Set basalt stone 13x9x5 for 1/4 sec. cor. from which

A Pine 5 in. dia. bears East 41 lks. dist.
A Pine 12 in. dia. bears S40°W, 60 lks. dist.

In 1917, U.S. Forest Service Surveyor, Frank J. Van Winkle, visited this corner during the course of his survey along the east boundary of Section 12. His record states:

The 1/4 sec. cor. in the E. Bdy of Sec. 12 is a stone 8 x 8 x 4 ins. above ground mkd. dimly 1/4 on W. face set in a small mound of stone, in a ravine.

Pine 7 ins. dia., bears E 41 lks dist. mkd. 1/4 S BT
Pine 14 ins. dia., bears S40°W, 60 lks. dist. mkd. 1/4 S BT

Description of Corner Evidence Found:

Found a 13"x9"x5" stone marked 1/4 and firmly set.

Ponderosa Pine, 12" dia., w/partially healed blaze and scribing visible, bears N89°46'E, 26.10 ft. (Orig. Rec: East, 27.06 ft./Van Winkle Rec: Same)

Ponderosa Pine, 24" dia., w/partially healed blaze and scribing visible, bears S39°29'W, 39.70 ft. (Orig. Rec: S40°W, 39.60 ft./Van Winkle Rec: Same)


Description of monument and accessories I established to perpetuate the original location of this corner:

Set 2-1/2"x30" aluminum pipe with 3-1/4" aluminum cap, stamped as shown on the DIAGRAM, 20" in the ground and raised a mound of stone around the monument. Place the original stone alongside the north side of the monument. From Which:

Douglas Fir, 16" dia., S80°45'W, 29.9 ft., scribed: 1/4 S12 BT
Ponderosa Pine, 16" dia., S62°15'E, 48.1 ft., scribed: 1/4 S 7 BT

Measurements to BT's taken with a magnetic compass, declination 20° East, and a nylon clad steel tape. Set steel fence post with Land Survey Monument (54-9) sign 5' north of the monument. Nailed a brass washer stamped PLS 2405 on blaze above BT scribe as taken this survey. Nailed Bearing Tree (54-3) signs above blaze and Land Survey Monument (54-9) signs on back of each tree as required. Painted a 6" red band above Bearing Trees signs and painted blaze red.

DIAGRAM



REGISTERED PROFESSIONAL LAND SURVEYOR

Susan E. Newstetter

OREGON JULY 26, 1889 SUSAN E. NEWSTETTER 2405

Exp: 12/31/94

This work was performed by: Susan E. Newstetter PLS 2405 Witnessed by: D. Mitchell Ferguson and Rick Saul October 20, 1992 Refer to Grant Co. Survey No.: 1239

Office of Surveyor County of Grant
State of OR I hereby certify that the within instrument was filed in this office for record on the 20 day of Jan., 1993
Shane D. Smith by _____
(COUNTY OFFICIAL) (DEPUTY)