

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner was established by H. D. Graddon and Bamford Robb, US Deputy Surveyors, during the original survey Joint Contract No. 383 dated March, 1881.

Set basalt stone 16x10x6 in stone mound, for 1/4 sec cor. from which

A pine 36 ins dia bears S10°E, (74.6') 113 lks dist

DIAGRAM

T11S R35E

S10
1/4—
S15

1986
PLS 699

Description of corner evidence found:

Found a stone mound, but could not find any stone with markings.

24" Ponderosa pine (3' Stump) (Scribing Visible) (1881 BT) bears S6° 15'E, 77.3 feet.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2"x30" aluminum pipe with a 3 1/4" aluminum cap, marked as shown in the diagram, 28" in the ground, in the center of the rock mound. Improved the existing mound with rock & earth to be 36" in diameter by 6" high around the monument, from which new BTs are:

4" Juniper bears N20°E, 125.2 feet scribed 1/4 S10 BT

9" Juniper bears S46° 15'E, 67.1 feet scribed 1/4 S15 BT

Attached BT and Attention signs to and painted a red band around each BT. Bearings were taken with a staff compass, using a declination of 18° 30'E, to stamped brass washers nailed in the scribed red-painted blazes. Distances were measured from a 60d spike, with an aluminum washer stamped PLS 699, which was driven into the side of each BT approximately one foot above the ground.

Set a steel fence post 5 feet W of the corner with an Attention sign attached. The monument is not a National Forest property corner.

I, Leland L. Myers, P.O. Box 98, Sumpter, OR 97877, do hereby certify that on July 18, 1986, I monumented the corner as herein described.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Leland L. Myers

OREGON
JULY 9, 1965
LELAND LEE MYERS
699

FILED

IN THE OFFICE OF THE Grant COUNTY SURVEYOR

THIS 6 DAY OF April, 1987

Robert D. Baggett
Grant County Surveyor