

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner was established by Herman D. Gradon and Bamford Robb, US Deputy Surveyors, during the original joint survey Contract No. 383 dated March, 1881.

Set basalt stone 14x8x6 for Cor. to Sec's 24, 25, 19 & 30

from which

- A pine 16 ins. dia. bears N55°E, (8.6')13 lks dist
- A pine 30 ins. dia. bears S70°E, (35.6')54 lks dist
- A pine 24 ins. dia. bears S66°W, (22.4')34 lks dist
- A pine 30 ins. dia. bears N75°W, (19.1')29 lks dist

DIAGRAM

T11S	
R35E	R35 1/2 E
S24	S21
S25	S28

1985
PLS 699

Description of corner evidence found:

A stone 16x8x6 with two other rocks and a small railroad rail driven in the ground.

- Ponderosa pine (Down & Rotting Away)(Blaze in Rotted Remains)(1881 BT) bears N58° 15'E, 8.5 feet.
- Ponderosa pine (Down & Rotting Away)(Blaze in Rotted Remains)(1881 BT) bears S65° 45'E, 36.8 feet.
- Ponderosa pine (Down & Rotting Away)(Blaze in Rotted Remains)(1881 BT) bears S69° 30'W, 21.8 feet.
- Ponderosa pine (Down & Rotting Away)(Blaze in Rotted Remains)(1881 BT) bears N78° 45'W, 18.9 feet.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2"x30" aluminum pipe with a 3 1/4" aluminum cap, marked as shown in the diagram, 22" in the ground to rock, replacing the rock which is turned upside down and buried on the north side of the monument. Built a mound of rock & earth to be 28" in diameter by 8" high around the monument, from which new BTs are:

- 9" Ponderosa pine bears S46°E, 39.4 feet scribed T11SR35 1/2 E S28 BT
- 7" Juniper bears N68° 30'E, 33.1 feet scribed T11SR35 1/2 E S21 BT
- 10" Ponderosa pine bears N3° 45'W, 112.1 feet scribed T11SR35E S24 BT
- 14" Ponderosa pine bears S63° 15'W, 25.1 feet scribed T11SR35E S25 BT

Attached BT and Attention signs to and painted a red band around each BT. Bearings were taken with a staff compass, using a declination of 18° 30'E, to stamped aluminum washers nailed in the scribed red-painted blazes. Distances were measured from a 60d spike, with an aluminum washer stamped PLS 699, which was driven into the side of each BT approximately one foot above the ground.

Set a steel fence post 5 feet E of the corner with an Attention sign attached. The monument is not a National Forest property corner.

I, Leland L. Myers, P.O. Box 98, Sumpter, OR 97877, do hereby certify that on August 25, 1985, I monumented the corner as herein described.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Leland Lee Myers

OREGON
JULY 9, 1955
LELAND LEE MYERS
699

FILED

IN THE OFFICE OF THE Grant COUNTY SURVEYOR

THIS 25 DAY OF Oct, 19 85

Robert D. Sayre Co. Sur.

See MAP OF SURVEY NO. 901