


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Center-North 1/16th corner not previously established.



Description of corner evidence found:

Established C-N 1/16th corner on the center of section line midway between the Center 1/4 corner and the North 1/4 corner.


Description of monument and accessories I established to perpetuate the original location of this corner See Map of Survey No. 311.

Set a 1 1/2" x 30" iron pipe 28 inches in the ground with brass cap marked as shown.

from which NEW BEARING TREES:

A P. pine, 18 ins. diam., bears N88°E., 53.3 ft., mkd. CN 1/16 S28 CS BT.

A P. pine 19 ins. diam., bears S.14°W., 21.6 ft., mkd., CN1/16 S28 CS BT.



This corner is 18 ft. west of a fence running north and south and 110 ft. north of a Forest Service road.

I surrounded the pipe with a mound of stone.

Used compass with 20° East variation and a steel tape, measuring to a nail in a brass washer driven into the BT blaze. Washer is marked " OPLS 598 ".

Office of County Surveyor County of Grant
 State of Oregon , I hereby certify that the within instrument was filed in this office
 for record on the 30th day of August 1973, at 1:55 o'clock P. m., (signed)
Robert D. Bagett County Surveyor by (DEPUTY)
 (COUNTY OFFICIAL)

Witnessed by *Darlene Lemon* August 30, 1973

