

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:  
Corner has not been previously set.

**DIAGRAM**

T11S R35E

W1/16  
C-----C  
525

1985  
PLS 699

Description of corner evidence found:  
Corner is being set by this survey.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2"x30" aluminum pipe with a 3 1/4" aluminum cap, marked as shown in the diagram, 24" in the ground rock, at a point as determined by the procedures set forth in the MANUAL OF INSTRUCTIONS FOR THE SURVEY OF PUBLIC LANDS for the subdivision of sections. Built a mound of rock to be 36" in diameter by 6" high around the monument, from which new BTs are:

- 7" Ponderosa pine bears S37° 30'W, 13.7 feet scribed CW1/16 525 BT
- 7" Ponderosa pine bears N16° 30'W, 12.1 feet scribed CW1/16 525 BT

Attached BT and Land Survey Monument signs to and painted a red band around each BT. Bearings were turned from the control traverse with a theodolite, basis of bearing being a solar observation, to stamped aluminum washers nailed in the scribed red-painted blazes. Distances were measured from a 60d spike, with an aluminum washer stamped PLS 699, which was driven into the side of each BT approximately one foot above the ground.

Set steel fence posts 5 feet W and 5 feet S of the corner on the National Forest property lines. Attached Forest Boundary signs to each post and a Land Survey Monument sign to the W post.

I, Leland L. Myers, P.O. Box 98, Sumpter, OR 97877, do hereby certify that on September 4, 1985, I established the corner as herein described.

**FILED**

IN THE OFFICE OF THE Grant COUNTY SURVEYOR  
THIS 25 DAY OF OCT, 19 85

*Robert D. Sargent Co. Sur.*

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*Leland L. Myers*

OREGON  
JULY 9, 1963  
LELAND LEE MYERS  
699

See MAP OF SURVEY NO. 901