

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner has not been previously set.

DIAGRAM

T11S R35E

C1/4S25

1985  
PLS 699

Description of corner evidence found:

Corner is being set by this survey.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2"x30" aluminum pipe with a 3 1/4" aluminum cap, marked as shown in the diagram, 22" in the ground rock, at a point as determined by the procedures set forth in the MANUAL OF INSTRUCTIONS FOR THE SURVEY OF PUBLIC LANDS for the subdivision of sections. Built a mound of rock & earth to be 36" in diameter by 8" high around the monument, from which new BTs are:

14" Lodgepole pine bears N18° 30'W, 166.6 feet scribed C1/4 S25 BT

9" Ponderosa pine bears N41° 30'E, 156.7 feet scribed C1/4 S25 BT

Attached BT and Land Survey Monument signs to and painted a red band around each BT. Bearings were turned from the control traverse with a theodolite, basis of bearing being a solar observation, to stamped aluminum washers nailed in the scribed red-painted blazes. Distances were measured from a 60d spike, with an aluminum washer stamped PLS 699, which was driven into the side of each BT approximately one foot above the ground.

Set a steel fence post 5 feet S of the corner with a Land Survey Monument sign attached. The monument is not a National Forest property corner.

I, Leland L. Myers, P.O. Box 98, Sumpter, OR 97877, do hereby certify that on September 4, 1985, I established the corner as herein described.

FILED

IN THE OFFICE OF THE Grant COUNTY SURVEYOR

THIS 25 DAY OF OCT, 1985

*Robert D. Baggett, Co. Sur.*

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*Leland L. Myers*

OREGON  
JULY 9, 1965  
LELAND LEE MYERS  
699

See MAP OF SURVEY NO. 901