

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


V-7

History of original corner establishment:

*Original corner established in 1881
by Robb & Graden.*

Set post from which:

*A 8" black pine brs. N10°W 40 lks.
A 6" black pine brs. S30°W 74 lks.*



MOS 1115

Description of corner evidence found: *Searched for, not found.*

Established corner position by single proportion.


Description of monument and accessories | established to perpetuate the original location of this corner: *Set 2 1/4" x 30" aluminum*

Cap marked

*pipe with 2 1/2" aluminum cap rising 4".
BTs*

*9" Tamarack brs. N47°E 4.2'
marked 1/4 529 BT*

*6" LP brs. S26°E 18.6'
marked 1/4 532 BT*



REGISTERED
PROFESSIONAL
LAND SURVEYOR

George W. Colvin, Jr.

OREGON
FEBRUARY 14, 1975
GEORGE W. COLVIN, JR.
1020

*I hereby certify the above corner
was established as described
in Oct. 1989.*

Office of County Surveyor County of Grant
State of Oregon I hereby certify that the within instrument was filed in this office
for record on the 1 day of Dec, 1989
Robert H. Bagg by _____
(COUNTY OFFICIAL) (DEPUTY)

V-7