

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner was established by Herman D. Gradon and Bamford Robb, US Deputy Surveyors, during the original joint survey Contract No. 383 dated March, 1881.

Set basalt stone 18x14x7 for Cor. to Sec's 25, 36, 30 & 31

from which

- A pine 24 ins. dia. bears N70°E, (91.1')138 lks dist
- A pine 28 ins. dia. bears S25E, (22.4')34 lks dist
- A pine 30 ins. dia. bears S60°W, (47.5')72 lks dist
- A pine 30 ins. dia. bears N50°W, (33.0')50 lks dist

DIAGRAM

T115	
R35E	R35 1/2 E
S25	S28
S36	S33

1985
PLS 699

Description of corner evidence found:

The corner stone with chisel marks was firmly set in the ground surrounded by stones.

- Ponderosa pine (Down & Rotting Away) (Blaze in Rotted Remains) (1881 BT) bears N70°E, 91.8 feet.
- 24" Ponderosa pine (Down & Rotting Away) (Blaze in Rotted Remains) (1881 BT) bears S23° 15'E, 22.5 feet.
- 26" Ponderosa pine (30" Stump) (Scribing Visible) (1881 BT) bears S60° 15'W, 47.9 feet.
- 28" Ponderosa pine (Fair Condition) (Scribing Visible) (1881 BT) bears N48° 30'W, 33.9 feet.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2"x30" aluminum pipe with a 3 1/4" aluminum cap, marked as shown in the diagram, 24" in the ground, replacing the rock which is turned upside down and buried on the north side of the monument. Built a mound of rock & earth to be 36" in diameter by 6" high around the monument, from which new BTs are:

- 8" Ponderosa pine bears S75°W, 7.3 feet scribed T11SR35E S36 BT
- 7" Ponderosa pine bears N22° 15'E, 26.9 feet scribed T11SR35 1/2 E S28 BT
- 7" Ponderosa pine bears S23° 15'E, 39.8 feet scribed T11SR35 1/2 E S33 BT

Attached BT and Attention signs to and painted a red band around each BT. Bearings were taken with a staff compass, using a declination of 18° 30'E, to stamped aluminum washers nailed in the scribed red-painted blazes. Distances were measured from a 60d spike, with an aluminum washer stamped PLS 699, which was driven into the side of each BT approximately one foot above the ground.

Set a steel fence post 5 feet S of the corner with an Attention sign attached. The monument is not a National Forest property corner.

I, Leland L. Myers, P.O. Box 98, Sumpter, OR 97877, do hereby certify that on July 31, 1985, I monumented the corner as herein described.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Leland Lee Myers

OREGON
JULY 9, 1985
LELAND LEE MYERS
699

FILED

IN THE OFFICE OF THE Grant COUNTY SURVEYOR

THIS 25 DAY OF OCT, 19 85

Robert D. Baggett
Co. Sur.

See MAP OF SURVEY NO. 901