

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. B-18

History of original corner establishment:

Grant County Survey Records show no previous establishment of this Cor.

DIAGRAM

T12S R30E
NW1/16
S2
1985
PLS 848

Description of corner evidence found:

Grant County Survey Records show no previous establishment of this Cor.

Description of monument and accessories | established to perpetuate the original location of this corner:

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the **DIAGRAM**, SET 26" in the ground.
From Which.
A Pine 14" dia., Bears N42°E., 12.9 ft., scribed: NW1/16 S2 BT
A Pine 8" dia., Bears N77°W., 18.4 ft., scribed: NW1/16 S2 BT
Measurements to trees taken with a metal tape and magnetic compass, with Declination set off 20 deg. East.
Nailed a brass washer stamped PLS 848 on blaze above BT scribe, Bearing Tree Sign above blaze, and warning sign on back of each tree. Painted a 6" red band at breast ht. around each tree. Set steel fence posts with warning & Boundary Signs, South 6 ft. and West 5 ft. from the corner.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson PLS 848
Mt. Vernon Oregon.
On: Oct. 11, 1985
Refer to Map of Survey No. 904

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 30 day of Dec, 1985
Robert D. DeGroot by _____
(COUNTY OFFICIAL) (DEPUTY)