

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. C-9


History of original corner establishment:

In Sept. 1881, under GLO Contract No. 415, Samuel W. Lackland set basalt stone 16x8x5 ins. 12 ins. in ground for 1/4 Sec. Cor. marked 1/4 on W. face from which:

A Pine 40" dia. bears N56° E., 53 lks. dist. marked 1/4 S BT.

A Pine 12 ins. dia. bears N47°W 56 lks. dist. marked 1/4 S BT.

DIAGRAM



Description of corner evidence found:

At corner location found painted stone in small mound of stones. Found both original BT's. The N.E. one is wind blown down and dead for some time. The N.W. BT is alive with opened blaze to visible scribing "S BT". The painted stone does not match the record bearings and dist. from the original BT's. The record dist. from the N.W. BT of 56 lks does not match the bearing to the N.E. BT. It is difficult distinguishing between 3's and 5's in Lackland's notes at times. Record dist. and bearings match very well if the dist. to the N.W. BT is 36 lks. and bearing N.E. BT is N36°E. The true location of the N.E. BT is unknown but is approximated from its down position on the ground. The painted stone is the wrong size, 23'x8"x8". Found a stone used in mound of stones lying loose on ground with faint " /4 " on a face. Possible original stone disturbed, size 16"x9"x6".

Description of monument and accessories established to perpetuate the original location of this corner:

At record bearing and distance from good original N.W. BT (S47°E 36 lks 23.76) set 2 1/2"x30" aluminum pipe with 3" aluminum cap stamped:

Set pipe 17" in ground to rock with mound of stones (from stone mound found). Buried possible original stone alongside.

T12S R30E
1/4
S5 + S4
1981
OR PLS 1294

Old BT's:

Wind blown dead P. Pine 40" dia. bears approx. N37°E., 35 ft. to approx. face of old blaze. Tree is rotted and no scribing could be seen.

A live P. Pine 25" dia. bears N47°W, 24.0 ft. to center of tree at base with opened blaze to visible scribing "S BT".

New BT:

A P. Pine 10" dia. bears N 15°E, 14.0 ft., scribed 1/4 S4 BT.

The painted stone was N 57°E., 5.85 ft. from mon. Used stones in mound of stones around mon.

Attached 54-3 and 54-4 signs to all BT's. Attached brass washer stamped LS 1294 to foot blaze of new BT. Painted blazes and 6" band around all BT's red. Attached 54-2 and 54-4 signs to metal post 8' South of corner.

Magnetic Declination = 19°30' E

I hereby certify the above corner monument was reestablished as herein described on June 17, 1981.

Witnesses: R. Orton
A. Hanley
G. Orton

Office of..... County Surveyor..... County of..... Grant.....
State of..... Oregon....., I hereby certify that the within instrument was filed in this office for record on the..... day of..... Aug....., 1981.....
by..... (COUNTY OFFICIAL)..... (DEPUTY)

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

OREGON
SEPTEMBER 23, 1977
HOWARD L. PERRY
1294