

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner not previously established.

DIAGRAM

T12S R30E
C1/4
S3
1982
PLS 848

Description of corner evidence found:

Corner not previously established.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 30"x2" aluminum pipe with a 3 1/2in. aluminum Cap. stamped as shown in diagram. Set 12" in ground. Raised a mound of large stone's around pipe.

From Which

A Pine 13" dia. bears S 36° E 4.9ft. scribed C1/4 S3 B.T.

A Pine 11" dia. bears N 67° E 23.4ft. scribed C1/4 S3 B.T.

Nailed brass washers stamped PLS 848, bearing tree and warning sign to each tree. Painted 6" red band around each tree.

Set steel posts with warning and boundry signs. 5.0ft. West and 4.0ft. South from corner.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Corner monumented 9-30-82
Witnessed by D. Mitchell Ferguson

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

Office of.....Surveyor..... County of.....Grant.....

State of.....Oregon... I hereby certify that the within instrument was filed in this office

for record on the...29th day of.....August....., 19..83.

Robert D. Bayart by
(COUNTY OFFICIAL) (DEPUTY)