

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner not preveously established.

DIAGRAM

T12S R30E
N1/16^CS12
1982
PLS 848

Description of corner evidence found:

Description of monument and accessories | established to perpetuate the original location of this corner:

Set a 30"x2" aluminum pipe with a 3½" aluminum Cap. stamped as shown in diagram, set 10" in the ground, & raised a mound of stone around the pipe.

From Which:

A Pine 10" dia. bears N8°E 14.2ft. scribed CN 1/16 S12 B.T.

A Pine 7" dia. bears S45°E 3.2ft. scribed CN 1/16 S12 B.T.

Nailed brass washers stamped PLS 848, B.T. & warning signs to each tree

Painted 6" red band around each tree.

Set steel posts with warning & boundry signs West 4.0ft. and South 4.0ft. from corner.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Witnessed by

Corner monumented 10-12-82

Witnessed by D. Mitchell Ferguson

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

Office of.....Surveyor..... County of.....Grant.....
State of.....Oregon....., I hereby certify that the within instrument was filed in this office
for record on the 29th day of.....August....., 19.83

.....
(COUNTY OFFICIAL) (DEPUTY)