

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. G-13

History of original corner establishment:

In Sept. 1881 under GLO Contract No. 415, Samuel W. Lackland set post 3 1/2 ft. long 4" square, 12 ins. in ground for 1/4 Sec. Cor. marked 1/4 on W. face from which:

A Tamarack 20 ins. dia. bears N32°W, 15 lks. dist. marked 1/4 S BT.

A Fir 10 ins. dia. bears S10°E, 19 lks. dist. marked 1/4 S BT.

DIAGRAM

T12S R30E
1/4
S9 + S10

Description of corner evidence found:

Area of 1/4 Cor. location has been heavily logged and S.W. Lackland blazed his BT from waist to chest high. Could find no evidence of the old BT's or original post.

Description of monument and accessories established to perpetuate the original location of this corner:

At single proportioned distance between the N.E. and S.E. Cor's. to Section 9, T12S, R30E, set 2 1/2" aluminum pipe with 3 1/4" aluminum cap stamped: Set pipe 25" in ground with mound of stone and soil to cap.

BT's:

A Grand Fir 6" dia. bears S51°W, 10.0 ft. scribed 1/4 S9 BT.

A Grand Fir 8" dia. bears S58°E, 9.3 ft. scribed 1/4 S10 BT.

T12S R30E
1/4
S9 + S10
1981
OR PLS 1294

Attached 54-3 and 5-4 signs to both BT's. Attached brass washer stamped LS 1294 to foot blaze of both BT's. Painted blazes and 6" band around both BT's red. Attached 54-2 and 54-4 signs to metal post 4' south of corner.

Magnetic Declination = 19°30'E

I hereby certify the above corner monument was reestablished as herein described on August 12, 1981.

Witnesses: R. Orton
A. Hanley
G. Orton



Office of... County Surveyor... County of... Grant
Oregon
State of... I hereby certify that the within instrument was filed in this office
for record on the... 6... day of... Aug... 1981
Robert L. Baggett by...
(COUNTY OFFICIAL) (DEPUTY)