

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

DIAGRAM

T12S R30E
W1/16 S10
S15
1982
PLS 848.

Description of corner evidence found:

Corner not previously established.

Description of monument and accessories established to perpetuate the original location of this corner:

Set a 30"x2" aluminum pipe with a 3½" aluminum Cap. stamped as shown in diagram, Set 24" in ground.

From Which:

A Pine 14" dia. bears N15°E, 11.0ft. scribed W1/16 S10 B.T.

A Pine 11" dia. bears S72°E, 35.0ft. scribed W1/16 S15 B.T.

Nailed brass washers stamped PLS 848, warning & bearing tree signs to each tree.

Painted 6" red band around each tree.

Set steel post with warning & boundry signs North 4.0ft. & East 5.0ft. from corner.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Corner monumented 10-13-82

Witnessed by D. Mitchell Ferguson

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

Office of.....Surveyor..... County of.....Grant.....

State of.....Oregon....., I hereby certify that the within instrument was filed in this office

for record on the 29th day of.....August....., 19.....83.

.....Robert D. Bager..... by
(COUNTY OFFICIAL) (DEPUTY)