

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner not previously established.

DIAGRAM

T12S R30E
S 1/16
S14 S13
1983
PLS848

Description of corner evidence found:

Corner not previously established.

Description of monument and accessories | established to perpetuate the original location of this corner:

Set a 30"x2" aluminum pipe with 3½" aluminum cap, stamped as shown in diagram.
Set 10" in the ground & raised a mound of stone around pipe.
From Which:
A Juniper 18" dia. bears N82°E, 98.6 ft. scribed S1/16 S13 BT.
A Juniper 13" dia. bears N72°W, 92.0 ft. scribed S1/16 S14 BT.
Nailed brass washers stamped PLS848, bearing tree & warning signs to each tree.
Set steel post with warning & boundry signs 5' East from corner.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

Corner monumented 4-19-83

Witnessed by D. Mitchell Ferguson

Office of.....Surveyor..... County of..... Grant
State of..... Oregon....., I hereby certify that the within instrument was filed in this office
for record on the 29th day of August, 1983.
Robert D. Baggett by
(COUNTY OFFICIAL) (DEPUTY)