

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner not previously established.

DIAGRAM

T12S R30E
SW1/16 S13
1983
PLS848

Description of corner evidence found:

Corner not previously established.

Description of monument and accessories | established to perpetuate the original location of this corner:

Set a 30"x2" aluminum pipe with a 3½" aluminum cap, stamped as shown in diagram.
Set 6" in the ground, and raised a mound of stone around pipe.

From Which:

A Juniper 8" dia. bears S25°W, 66.0 ft. scribed SW 1/16 S13 BT.

A Juniper 8" dia. bears N39°W, 90.2 ft. scribed SW 1/16 S13 BT.

Nailed brass washers stamped PLS848, with bearing tree & warning signs to each tree.

Set steel posts with warning & boundry signs South 10' & West 5' from the corner.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Douglas M. Ferguson
OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

Corner monumented 4-19-83

Witnessed by D. Mitchell Ferguson

Office of.....Surveyor..... County of.....Grant.....

State of.....Oregon....., I hereby certify that the within instrument was filed in this office

for record on the 29th day of.....August....., 1983.

Robert W. Bayett by
(COUNTY OFFICIAL) (DEPUTY)