

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner not previously established,

DIAGRAM

T12S R30E
S\$3
W1/16 S24
1983
PLS848

Description of corner evidence found:

Corner not previously established.

Description of monument and accessories established to perpetuate the original location of this corner:

Set a 30"x2" aluminum pipe with a 3½" aluminum cap, stamped as shown in diagram.
Set 10" in the ground & raised a mound of stone around pipe.
From Which:
A Pine 8" dia. bears S22°W, 48.4 ft. scribed W1/16 S24 BT.
A Pine 10" dia. bears N18°W, 44.8 ft. scribed W1/16 S13 BT.
Nailed brass washers stamped PLS848, with bearing tree & warning signs to each tree.
Set steel posts with warning & boundry signs North & West 5 ft.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

Corner monumented 4-15-83

Witnessed by D. Mitchell Ferguson

Office of.....Surveyor..... County of.....Grant.....
State of.....Oregon....., I hereby certify that the within instrument was filed in this office
for record on the...29th...day of.....August....., 19..83.
.....Robert D. Bager..... by
(COUNTY OFFICIAL) (DEPUTY)