


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner not previously established.



Description of corner evidence found:

Corner not previously established.

Description of monument and accessories established to perpetuate the original location of this corner:

Set a 30"x2" aluminum pipe with a 3½" aluminum cap, stamped as shown in diagram.
Set 20" in the ground & placed a ring of stone around pipe.

From Which:

A Fir 10" dia. bears N41°W, 11.7 ft. scribed C S1/16 S21 BT.

A Juniper 11" dia. bears S81°E, 27.8 ft. scribed C S1/16 S21 BT.

Nailed brass washers stamped PLS848, with bearing tree & warning signs to each tree.

Set steel posts with warning & boundary signs South 4 ft. & West 4 ft.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Douglas M. Ferguson
OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

Corner monumented 10-26-82

Witnessed by D. Mitchell Ferguson

Office of.....Surveyor..... County of..... Grant.....
State of.....Oregon....., I hereby certify that the within instrument was filed in this office
for record on the 29th day of.....August....., 1983.
Robert D. Bazzell by
(COUNTY OFFICIAL) (DEPUTY)