


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1881 by S.W. Lackland, under General Land Office Contract No. 415 Surveyor Generals notes states: Set basalt stone 16x10x8 ins. 12 ins in ground for corner to sec. 19, 30, 24 & 25 marked with 2 notches on South & 4 notches on N edged: From which:

A Pine 16" dia. bears N 20°W, 50 lks marked T12S R29E S24 BT.
A Pine 12" dia. bears S 34°E, 30 lks marked T12s R30E S30 BT.
A Pine 12" dia. bears S 72°W, 80 lks marked T12S R29E S25 BT.
A Pir 20" dia. bears N81°E 69 lks marked T12S R30E S19 BT.

In 1958 H.E. Taylor performed th following as per his notes. I scribed new BT's as follows
On West boundary T 12 S R 30 E W.M. Found orig stone 10" Fir N12W 45.0ft. "S24 BT"
(Orig. 16" Pine N 20 W 33ft.) now windfall with scribe. (Orig. 12" Pine S36E 19.8ft
(Orig. 12" Pine S36E 19.8ft. Now 16") Good Condition. 8" Fir N5E 31.4ft. "S19 BT"
(Orig. 12" Pine S72W 52.8 ft. Now 24") ok with tag.
(Orig. 20" Fir N81 East 45.5 ft. Now 20") rotted windfall with scribe.



Description of corner evidence found:

Found stone 16 x 8 x 6 set in mound. 2 notches on S-Face & 4 notched on N-Face are visible.

From which:

A Pine 18" dia. bears S57°W 54.6 ft. scribing visible.
A down Pine 12" dia. bears S45°E 18.7 ft. scribing visible.
Found trees as scribed by H.E. Taylor as per his calls.
Bearing Trees don't fit original calls.
However stone is in original position. Accepted stone as corner position.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 30" x 2" aluminum pipe with 3½" aluminum cap, stamped as shown in diagram.

Set monument 25" in ground.

Placed a ring of stone around pipe.

Set original stone North alongside.

From which:

A Fir taken by Taylor 12" dia. bears N 15°W 45.0 ft. I scribed T12S R29E S24 BT.

A Fir taken by Taylor 13" dia. bears N 5°E 31.4 ft. I scribed T12 R30E S19 BT.

A Fir 5" dia. bears S20°E. 5.7 ft seribed S 30 BT.

A Fir 10" dia. bears S70°W 21.7 ft. scribed T12S R29E S25 BT.

Nailed Brass washers stamped PLS 848, Bearing Tree & warning signs to each tree. Painted 6" red band around each tre..

Set steel post with boundary & warning signs E-W & S 4 ft. from corner.

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

Douglas M. Ferguson
OREGON
 JULY 12, 1988
DOUGLAS M. FERGUSON
 848

Date May 20, 1983

Witnessed by Dan Martin

Office of.....Surveyor..... County of.....Grant.....
 State of.....Oregon....., I hereby certify that the within instrument was filed in this office
 for record on the 29th day of August, 1983.
Robert D. Beyer by
 (COUNTY OFFICIAL) (DEPUTY)