

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1881 by S.W. Lackland, under General Land Office Contract No. 415, Surveyor General's notes state: Set basalt stone 20 x 14 x 12 ins., 13 ins. in ground for corner to sections 19, 20, 29, & 30 marked with 2 notches on S & 5 notches on E edges. Raised mound of stone 2½ ft. high 5 ft. base alongside.

DIAGRAM

T12S R30E
S19 | S20
S30 | S29
1983
PLS 848

Description of corner evidence found:

No evidence found. There has been no activity in area. Searched area thoroughly. No original accessories established position reluctantly set by proportion.

Description of monument and accessories established to perpetuate the original location of this corner:

Set 30" x 2" aluminum pipe with 3½" aluminum cap, stamped as shown in diagram.
Set monument 18" in ground, raised mound of stone & earth around pipe.
From which:
A Pine 13" dia. bears N48°W, 2.5 ft. scribed T12S R30E S19 BT.
A Pine 12" dia. bears N48°E, 16.6 ft. scribed T12S R30E S20 BT.
A Pine 9" dia. bears S72°E, 5.4 ft. scribed T12S R30E S29 BT.
A Pine 8" dia. bears S28°W, 34.3 ft. scribed T12S R30E S30 BT.
Nailed brass washer stamped PLS 848, Bearing Tree & warning sign to each tree.
Set steel post with boundary & warning sign east & south 4 ft. from corner.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Date May 18, 1983

Witnessed by Dan Martin

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

Office of.....Surveyor..... County of.....Grant.....
State of.....Oregon....., I hereby certify that the within instrument was filed in this office
for record on the.....29th day of.....August....., 19.....83.
.....by
(COUNTY OFFICIAL) (DEPUTY)