

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1881 by S.W. Lackland, under General Land Office Contract No. 415 Surveyor Generals Notes State:
Set basalt stone 22x10x12ins. 16ins. in ground for Cor. to Secs 20, 21, 28 & 29 marked with 2 notches on S & 4 notched on E edges.
Raised mound of stone 2½ft. high 5ft. base alongside.

DIAGRAM

T12S R30E
S20|S21
S29|S28
1982
PLS 848

Description of corner evidence found:

Corner evidence found: Set in rocky ground, below in rock; No evidence found;
Set corner by proportion.

Description of monument and accessories | established to perpetuate the original location of this corner:

Set a 30"x2" aluminum pipe with a 3½" aluminum Cap. stamped as shown in diagram.
Set 14" in ground, & raised a mound of stone around pipe.

From Which:

A Pine 8" dia. bears N29°E, 32.0ft. scribed T12S R30E S21 B.T.

A Juniper 14" dia. bears N32°W, 66.4ft. scribed T12S R30E S20 B.T.

A Juniper 7" dia. bears S12°E, 70.6ft. scribed T12S R30E S28 B.T.

A Mahogany 4" dia. bears S68°W, 54.5ft. scribed X B.T.

Nailed brass washers stamped PLS 848, warning & bearing tree signs to each tree. Painted 6" red band around each tree.

Set steel posts with warning & boundry signs North 4.0ft., East 4.0ft., South 5.0ft. & West 2.0ft from corner.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Corner monumented 10-26-82
Witnessed by D Mitchell Ferguson

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

Office of.....Surveyor..... County of...Grant.....
State of.....Oregon....., I hereby certify that the within instrument was filed in this office
for record on the 29th day of August, 1983

Douglas M. Ferguson by
(COUNTY OFFICIAL) (DEPUTY)