

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

**History of original corner establishment:**

Corner not previously established.

**DIAGRAM**

T12S R30E  
E1/16  $\frac{S23}{S26}$   
1983  
PLS848

**Description of corner evidence found:**

**Description of monument and accessories I established to perpetuate the original location of this corner:**

Set a 30"x2" aluminum pipe with 3½" aluminum cap, stamped as shown in diagram.  
Set 20" in ground.

From Which:

A Juniper 8" dia. bears S50°W, 3.5 ft. scribed E1/16 S26 BT.

A Juniper 5" dia. bears N63°E, 10.9 ft. scribed E1/16 S23 BT.

Nailed brass washers stamped PLS848 bearing tree & warning signs to each tree.

Set steel post with warning & boundry sign 5' E from corner.

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

OREGON  
JULY 12, 1968  
DOUGLAS M. FERGUSON  
848

Corner monumented 4-20-83

Witnessed by Dan Martin

Office of.....Surveyor..... County of..... Grant.....  
State of..... Oregon....., I hereby certify that the within instrument was filed in this office  
for record on the...29th day of... August... 19... 83.  
..... Robert D. Beyer..... by .....  
(COUNTY OFFICIAL) (DEPUTY)