

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner not previously established.

DIAGRAM

T12S R30E
N1/16
S28 S27
1983
PLS 848

Description of corner evidence found:

Corner not previously established.

Description of monument and accessories established to perpetuate the original location of this corner:

Set 30" x 2" aluminum pipe with 3½" aluminum cap, stamped as shown in diagram.

Set monument 24" in ground.

From which:

A Fir 9" dia. bears S74°W, 3.6 ft. scribed N1/16 S28 BT.

A Fir 12" dia. bears S47°E, 32.9 ft. scribed N1/16 S27 BT.

Nailed brass washers stamped PLS 848, bearing tree & warning signs to each tree.

Painted 6" red band around each tree.

Set steel post with boundary & warning signs S 3.0 & E 5.0 from corner.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Date May 12, 1983

Witnessed by Dan Martin

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

Office of.....Surveyor..... County of.....Grant.....

State of.....Oregon....., I hereby certify that the within instrument was filed in this office

for record on the..29th day of.....August....., 19..83.

.....by.....
(COUNTY OFFICIAL) (DEPUTY)