

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner not previously established.

DIAGRAM

T12S R30E
C1/4
S27
1983
PLS 848

Description of corner evidence found:

Corner not previously established.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 30" x 2" aluminum pipe with 3½" aluminum cap, stamped as shown in diagram.

Set monument on solid rock,,raised mound of stone 28" high 36" dia. around pipe.

From which:

A Juniper 7" dia. bears N 66½° W, 22.8 ft. scribed C1/4 S27 BT.

A Juniper 7" dia. bears N 6° E, 46.2 ft. scribed C1/4 S27 BT.

Nailed brass washers stamped PLS 848, bearing tree & warning signs to each tree.

Painted 6" red band around each tree.

Set steel post with warning sign N 5 ft. from corner.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Douglas M. Ferguson
OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

Date May 12, 1983

Witnessed by Dan Martin

Office of.....Surveyor..... County of.....Grant.....
State of.....Oregon....., I hereby certify that the within instrument was filed in this office
for record on the...29th...day of.....August....., 19...83.
Robert D. Egan by
(COUNTY OFFICIAL) (DEPUTY)