

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1881 by S.W. Lackland, Under General Land Office Contract No. 415. Surveyor Generals Notes State:
Set basalt stone 15x12x6 in. 10 in. in ground for $\frac{1}{4}$ section corner, marked $\frac{1}{4}$ on West face. From Which a Fir 12" dia. bears N18°E, 4 lks. dist. marked $\frac{1}{4}$ S BT. A Fir 14" dia. bears N86°W, 12 lks. dist. marked $\frac{1}{4}$ S BT.

DIAGRAM

T12S R30E
S27 $\frac{1}{4}$ S26
1983
PLS848

Description of corner evidence found:

Found a 14" Fir dead & standing scribed $\frac{1}{4}$ S BT. Scribing does not conform with that of S.W. Lackland nor is it old enough to be original. No reliable evidence found, due to logging activity.

Set corner by proportion.

Found original stone lying loose in skid trail just downhill (East) from proportion position.

Description of monument and accessories | established to perpetuate the original location of this corner:

Set a 30"x2" aluminum pipe with a 3 $\frac{1}{2}$ " aluminum cap, stamped as shown in diagram. Set 20" in the ground & raised a mound of stone around pipe. Placed original stone North alongside.

From Which:

A Fir 6" dia. bears N64°W, 18.7 ft. scribed $\frac{1}{4}$ S27 BT.

A Fir 10" dia. bears S60°E, 57.8 ft. scribed $\frac{1}{4}$ S26 BT.

Nailed brass washers stamped PLS848, bearing tree & warning signs to each tree.

Painted 6" red band around each tree.

Set steel post with warning sign North from corner.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Douglas M. Ferguson
OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

Corner monumented 12-83

Witnessed by Dan Martin

Office of.....Surveyor..... County of.....Grant.....

State of.....Oregon....., I hereby certify that the within instrument was filed in this office

for record on the 29th day of.....August....., 19.83.

Robert D. Bazar by
(COUNTY OFFICIAL) (DEPUTY)