

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner not previously established.

DIAGRAM

T12S R30E
E1/16
C---C
S26
1983
PLS848

Description of corner evidence found:

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 30"x2" aluminum pipe with 3½" aluminum cap, stamped as shown in diagram.
Set 26" in the ground.

From Which:

A Fir 6" dia. bears N68°E, 10.5 ft. scribed CE1/16 S26 BT.

A Fir 5" dia. bears S21°W 7.5 ft. scribed ~~CE1/16~~ X BT.

Nailed brass washers stamped PLS848, bearing treex& Warning signs to each tree.

Set steel post N 4.0 ft. & S 20.0 ft. with boundry & warning signs.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

[Signature]
OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

Corner monumented 4-20-83

Witnessed by Dan Martin

Office of.....Surveyor..... County of.....Grant.....

State of.....Oregon....., I hereby certify that the within instrument was filed in this office

for record on the.....29th day of.....August....., 19.....83.

[Signature] by
(COUNTY OFFICIAL) (DEPUTY)