

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner not previously established.

DIAGRAM

T1T\$2SR30E
S1/16
S27 S26
1983
PLS848

Description of corner evidence found:

Description of monument and accessories | established to perpetuate the
original location of this corner:

Set a 30"x2" aluminum pipe with a 3½" aluminum cap, stamped as shown in diagram.
Set 24" in the ground.

From Which:

A Pine 10" dia. bears S16°W, 12.6 ft. scribed S1/16 S27 BT.

A Pine 9" dia. bears S27°E, 8.2 ft. scribed S1/16 S26 BT.

Nailed brass washers stamped PLS848, with warning & bearing tree signs to each tree.

Set steel posts with warning & boundry signs South 5 ft. & East 5 ft. from the corner.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

Corner monumented 5-3-83
Witnessed By Dan Martin

Office of.....Surveyor..... County of.....Grant.....
State of.....Oregon....., I hereby certify that the within instrument was filed in this office
for record on the 29th day of.....August....., 19.....83.
.....Robert D. Bryant..... by
(COUNTY OFFICIAL) (DEPUTY)