

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1881 by S. W. Lackland, under General Land Office Contract No. 415 Surveyor Generals notes state: Set basalt stone 15 x 8 x 7 ins. 10 ins. in ground for $\frac{1}{4}$ section corner marked $\frac{1}{4}$ on North face, from which:
A Pine 30 ins. dia. bears N87°W, 120 lks. dist. marked $\frac{1}{4}$ S BT.
A Pine 42 ins. dia. bears S72°W, 79 lks. dist. marked $\frac{1}{4}$ S BT.

DIAGRAM

T12S R30E
 $\frac{1}{4}$ S27
 $\frac{1}{4}$ S34
1983
PLS 848

Description of corner evidence found:

Found 36" Pine, live in good condition scribed $\frac{1}{4}$ S BT. Located a point at record S87°E, 79.2 ft. from the tree. Found 13 x 8 x 7 ins. stone marked $\frac{1}{4}$, down slope from position. Found remains of other BT confirming position.

Description of monument and accessories established to perpetuate the original location of this corner:

Set a 30" x 2" aluminum pipe with 3 $\frac{1}{2}$ " cap, stamped as shown in diagram. Set monument 10" in ground, raised mound of stone around pipe set original stone west alongside. From which:
A Juniper 12" dia. bears N188°E, 11.1 ft. scribed $\frac{1}{4}$ S27 BT.
A Pine 9" dia. bears S7°E, 30.2 ft. scribed $\frac{1}{4}$ S34 BT.
Nailed brass washers stamped PLS 848, Bearing Tree & warning signs to each tree.
Painted 6" red band around each tree.
Set steel post with warning sign 3 ft. North.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Douglas M. Ferguson
OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

Date May 14, 1983

Witnessed by Dan Martin

Office of.....Surveyor.....County of.....Grant
State of.....Oregon.....I hereby certify that the within instrument was filed in this office
for record on the.....29th.....August.....83.
Robert D. Begett by.....
(COUNTY OFFICIAL) (DEPUTY)