

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1881 by, S.W. Lackland, Under General Land Office Contract No. 415, Surveyor Generals Notes State:
Set basalt stone 18x12x9, 13 in. in ground for corner to sections 26, 27, 34, & 35, marked with 2 notches on E and 1 notch on S edges, raised a mound of stone 3 ft. high 5ft. base alongside.

DIAGRAM

T12S12R30E
S27 | S26
S34 | S35
1983
PLS848

Description of corner evidence found:

Found a small mound of stone look to be about 20 years old. Found on approx. corner position post. No conclusive evidence found, E & S fence corner, 12' S, N-S fence line & N & W fence corner approx. 250' South of search area, fencing in the area has destroyed all evidence. Set corner position by proportion.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 30"x2" aluminum pipe with 3½" aluminum cap, stamped as shown in diagram. Set 12" in ground & raised a mound of stone around pipe.

From Which:

A Pine 10" dia. bears N11°W, 36.4 ft. scribed T12S R30E S27 BT.

A Juniper 12" dia. bears N44°E, 58.7 ft. scribed T12S R30E S26 BT.

A Juniper 10" dia. bears S16°E, 20.7 ft. scribed T12S R30EES35 BT.

A Juniper 10" dia. bears S62°W, 34.8 ft. scribed T12S R30E S34 BT.

Nailed brass washers stamped PLS848, bearing tree & warning signs to each tree.

Set steel posts with warning & boundry signs North 4.0 ft. & East 4.0 ft. from corner.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Douglas M. Ferguson
OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

Corner monumented 5-3-83

Witnessed by Dan Martin

Office of.....Surveyor..... County of.....Grant.....

State of.....Oregon....., I hereby certify that the within instrument was filed in this office

for record on the 29th day of.....August....., 1983.

Robert D. Baggett by
(COUNTY OFFICIAL) (DEPUTY)