

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner not previously established.

DIAGRAM

T12S R30E
W1/16 $\frac{S26}{S35}$
1983
PLS848

Description of corner evidence found:

Description of monument and accessories | established to perpetuate the original location of this corner:

Set a 20"x2" aluminum pipe with a 3½" aluminum cap, stamped as shown in diagram.
Set 12" in the ground & raised a mound of stone around pipe.
From Which:
A Juniper 13" dia. bears N81°E, 42.0 ft. scribed W1/16 S26 BT.
A Juniper 9" dia. bears S58°W, 23.4 ft. scribed W1/16 S35 BT.
Nailed brass washers stamped PLS848, bearing tree & warning signs to each tree.
Set steel posts with warning & boundry signs North 12 ft. & West 5 ft. from corner.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

Corner moumented 5-3-83

Witnessed by D. Mitchell Fergusom

Office of.....Surveyor..... County of.....Grant.....
State of.....Oregon....., I hereby certify that the within instrument was filed in this office
for record on the..29th day of.....August....., 19..83.
.....Robert O. Baggett by.....
(COUNTY OFFICIAL) (DEPUTY)