

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

HISTORY OF ORIGINAL CORNER ESTABLISHMENT:

None. Corner established this survey.

DIAGRAM

T12S R30E
W 1/16
C—C
S31
1991
PLS 848

DESCRIPTION OF CORNER EVIDENCE FOUND:

None. Corner established this survey.

DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the DIAGRAM, 5" in the ground and raised a mound of stone 4 ft. in diameter, 2 1/2 ft. high around the monument.

From Which:

A Juniper, 14" dia., bears N72°30'E, 20.0 ft., scribed: C-W 1/16 S31 BT

A Juniper, 8" dia., bears S51°30'E, 46.6 ft., scribed: C-W 1/16 S31 BT

Measurements to BT's taken with an Electronic Tacheometer with bearings based on the survey control network.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1983
DOUGLAS M. FERGUSON
848

This work is performed by:

Douglas M. Ferguson PLS 848

Witnessed by:

D. Mitchell Ferguson & Rick Saul

August 8, 1991

Refer to Grant Co. Map of Survey No. 1185

Office of Surveyor County of Grant
State of OREG hereby certify that the within instrument was filed
in this office for record on the 27 day of SEPT, 1991
Robert D. Beyer by _____
(COUNTY OFFICIAL) (DEPUTY)